

PC Grabber™

PC Based DTMF Decoder • Model 1



Innovative Communications
TSI Products



PC Grabber™
Model 1

To install the PC GRABBER™ for Windows

- 1) If you are using a virus detection utility, disable it before running Setup. If you do not disable the utility, Setup may conflict with it and not run.
- 2) Start Windows after you have closed all other open applications.
- 3) Insert the PC GRABBER™ Setup disk in Drive A or B.
- 4) In the Windows Program Manger, Choose run from the start menu (Windows 95).
- 5) Select setup.exe (Windows 95) or in the Command Line box type the letter of the drive that contains the setup disk, followed by the command:\winpcg/setup.
- 6) Choose the OK button, and then follow the directions on the screen.

To install PC GRABBER™ Hardware on your computer

- 1) Connect the PC GRABBER™ interface to parallel port 1.
- 2) **WARNING: Do NOT connect the PC GRABBER™ interface to the serial port of your computer!**
- 3) The RJ11 interface on the PC GRABBER™ is for connecting to the telephone network or other circuit that is being tested. A cord with Alligator clips is included with the PC GRABBER™ for connecting to terminal blocks or jacks.

PC Grabber™ • Model 1 Users Manual

Telsoft Inc. • 10670 West Executive Drive • Boise, Idaho 83713
Tel: 208-658-7398 • Fax: 208-658-7687 • Email: telsoft@telsoftinfo.com
Web Page: www.telsoftinfo.com